VERY GREEN

- ANIMAL FRIENDLY
- 98% EFFECTIVE
- 20 TIMES LESS SOIL LOSS THAN STRAW WATTLES
- LOWER TURBIDITY
- CLEANER STREAMS
- MOVEABLE / REUSABLE
- RECYCLED MATERIALS

TEST RESULTS:

SAN DIEGO STATE UNIVERSITY SOILS LAB LA BASIN 10-YR STORM EQUIVALENT 3:1 SLOPE



98% EFFECTIVE

GATOR GUARD STRAW WATTLE

1 KG SOIL LOSS 20 KG SOIL LOSS



STRAW WATTLE

20 KG SOIL LOSS
55% EFFECTIVE

NO TREATMENT
45 KG SOIL LOSS
0% EFFECTIVE

FOAM LOGS - 4,6,8,9-in x 25-ft DRIVE-OVER CONTAINMENT BERM



USE GATOR GUARD IN PLACE OF SILT FENCE OR STRAW WATTLES

Q: MY SWPPP DRAWINGS SHOW SILT FENCE AND FIBER ROLLS. HOW CAN I USE GATOR GUARD WATTLES AS AN ALTERNATIVE BMP?

A: MOST AGENCIES ALLOW AND ENCOURAGE EQUAL OR BETTER PRODUCTS TO BE SUBSTITUTED FOR SILT FENCE AND FIBER ROLLS. JUST WRITE IN THE SUBSTITUTION ON YOUR PLAN, SIGN AND DATE IT. IF IN DOUBT, CHECK WITH YOUR AGENCY FIRST.

DO NOT USE GATOR GUARD WHERE A BIODEGRADABLE PRODUCT IS REQUIRED.


Gator Guard

Environmental Products Inc. ™

OFFICE: 10645 W SKYCREST ST. BOISE ID 83713 SHIPPING: 501 E 46TH ST. #5 BOISE ID 83714 PHONE: 877-428-6763 FAX: 208-608-5826

E-MAIL: SALES@GATORGUARD.COM

www.gatorguard.com



Distributed by: Bowman Construction Supply, 10801 E. 54th Avenue, Denver, CO 80239;

Phone: (303) 696-8960

Gator Guard

Environmental Products Inc. ™

www.gatorguard.com



SEDIMENT CONTROL WATTLE - STANDARD & EXTREME FOAM



NEW WEIGHTED WATTLES & WEIGHTED GUTTER WATTLES

ECONOMICAL AND GREEN, EVEN FOR SINGLE USE





SURVIVES TIRES & TRACKS

BUT, DRIVING OVER ANY BMP IS NOT RECOMMENDED. IT WILL IMMEDIATELY OR EVENTUALLY DESTROY IT AND CAN CAUSE TRACK-OUT AND LITTER.

5 YEAR EXPECTED LIFE



WATTLES 6-IN DIAMETER X 25-FT

A 6-IN GATOR GUARD WATTLE HAS 5-IN OF FREEBOARD - SAME AS A 9-IN STRAW WATTLE IN A 4-IN TRENCH

LIGHTWEIGHT, 10 POUNDS EACH
INSTALL WITH SHOVEL & HAMMER

Gator Guard Environmental Products Inc. TM



YES THEY WORK

(8-IN APRON MINIMIZES WASHOUTS)

EASY INSTALL, EASY REMOVAL

- PREPARE A SMOOTH 12-IN WIDE PATH
- NAIL UPHILL APRON EVERY 3-FT
- CONNECT WATTLES WITH SLEEVE
- PLACE 1-IN OF DIRT ON APRON
- ALTERNATE INSTALL PLACE APRON IN A 3-INCH TRENCH AND BACKFILL
- TO MOVE OR REMOVE, JUST PULL IT UP BY-HAND

LOW MAINTENANCE

- Remove excess sediment after storms
- REPAIR CUTS WITH CAULK, PICK UP FOAM
- DISPOSE OF WATTLE PROPERLY IF DAMAGED, DETERIORATED OR NO LONGER NEEDED



STANDARD FOAM

EXTREME FOAM

WHAT'S INSIDE?

- MONOFILAMENT GEOTEXTILE STUFFED WITH CLOSED CELL RECYCLED FOAM
- EACH WATTLE CONTAINS 22 5-INCH DECKNAILS + 2-ZIP TIES FOR CUT-TO-FIT AND REPAIRS
- EXTREME WATTLE MAINTAINS ALMOST FULL HEIGHT AFTER REPEATED DRIVE-OVERS
- REQUEST FREE MINI-SAMPLES FROM YOUR DEALER OR CALL GATOR GUARD



WEIGHTED GUTTER WATTLE

MORE PRODUCTS:

DITCH CHECKS, CHECK DAMS
VINYL CHANNELS & DIVERSIONS
FOAM GUTTER WATTLES (GLUE DOWN)
STORM DRAIN PROTECTION
TUBE STEPS

CUSTOM PRODUCTS - JUST CALL