


Section 1. Identification

GHS Product Identifier	: Matrix™ 502 Asphaltic Expansion Joint Backer Rod
Supplier	: The D.S. Brown Company 300 East Cherry Street North Baltimore, Ohio 45872 419-257-3561
In Case of Emergency	: Chemtrec 1-800-262-8200 International 01-703-741-5500
Information Department	: Environmental, health and safety department.

Section 2. Hazards Identification

A flammable hydrocarbon gas is used as a blowing agent in Polyethylene Foam. Trace amounts of this gas may remain in the product at the time of shipment. Note: Read the entire SDS for a more thorough evaluation of the hazards.

GHS Label Elements Pictograms	: 
Signal Word	: Not applicable.
Hazard Statements	: Not applicable.

POTENTIAL HEALTH EFFECTS:

Eye	: Dust may cause irritation or eye injury due to mechanical action. Fumes/vapors emitted during hot-wire cutting may cause eye irritation.
Skin	: Non-irritating to skin. Skin absorption is unlikely.
Inhalation	: Dust may cause irritation to the nose, throat and lungs. Fumes/vapors generated during hot-wire cutting may cause respiratory irritation. Concentrations of the isobutane agent incidental to proper handling of the product are expected to be well below the ACGIH recommended exposure limit of 800 ppm.
Ingestion	: None determined.
Systemic Effects (Other Target Organs)	: None determined.
Carcinogenicity	
NTP	: Not listed.
IARC	: Not listed.
OSHA Medical Conditions	: Not regulated.
Aggravated by Exposure	: None determined.



Bridge the World with Leading Infrastructure Solutions

Section 3. Composition/Information on Ingredients

CAS No.	Ingredient Name	%
009002-8804	Polyethylene	85-100
N/A	Other Proprietary Additives	5-15

Hazardous Components

CAS No.	Ingredient Name	Exposure Limits Wt. %
000075-28-5	Isobutane	800 ppm TWA (ACGIH)

Section 4. First Aid Measures

Eye	: Flush eyes with clean, lukewarm water (low pressure) occasionally lifting eyelids.
Ingestion	: Consult physician.
Skin	: Wash with soap and water.
Inhalation	: Remove to fresh air. If not breathing, give artificial respiration. Oxygen may be given by qualified personnel if breathing is difficult. Get medical attention.

Section 5. Fire-Fighting Measures

Flash Point	: -117°F (Isobutane)
Method Used	: TOC
Flammability Limits	: LFL 1.8% by volume : UFL 8.4% by volume (Isobutane)
Extinguishing Media	: Water
Special Firefighting Procedures	: Full emergency equipment with pressure demand self-contained breathing apparatus and full protective clothing should be worn by firefighters. During a fire, irritating and heavy toxic gases may be generated by thermal decomposition or combustion.

Section 6. Accidental Release Measures

Spill or Leak Procedures:	: No special precautions are necessary. This product is a non-hazardous waste when spilled or disposed of, as defined in Resource Conservation and Recovery Act (RCRA) regulations (40 CFR 261).
----------------------------------	--

Section 7. Handling and Storage

- Special Precautions** : Flammable vapors of isobutane may be generated during unventilated storage of large amounts of this product (for example, in storage trailers).
- To prevent the build-up of flammable vapors, do not store large quantities of this product in unventilated spaces including trailers. Ventilated trailers are recommended for transportation of bulk shipments of this product.
- To prevent potential fire or explosion, do not weld or apply intense heat to closed containers which contain this product. Open closed containers in a well ventilated area away from sparks or open flames.
- This product is combustible and should not be exposed to sparks or open flames. Large quantities of this product can burn rapidly and release toxic gases, including carbon monoxide.
- Fabrication methods involving cutting of large quantities of this product may release isobutane remaining in the foam cell structure. Provide adequate ventilation to ensure that isobutane concentrations remain below the ACGIH threshold limit value (TLV) of 800 ppm and the Lower Flammable Limit of 1.8% in air by volume to protect workers and eliminate the possibility of developing flammable or hazardous concentrations.

Section 8. Exposure Controls/Personal Protection

- Engineering Controls** : Provide general and/or local exhaust ventilation to control airborne isobutene levels below ACGIH Threshold Limit Value (TLV) of 800PPM.
- Eye Protection Requirements** : Wear tight fitting safety goggles if there is a potential for exposure to flying particles.
- Skin Protection Requirements** : No special precautions.
- Respiratory Protection Requirements** : No protection is required if isobutane levels are maintained below the ACGIH TLV of 800 ppm. For exposures above the TLV, take into consideration the type of application, environmental concentrations and materials being used concurrently when selecting a respirator. Observe OSHA regulations for respirator use (29 CFR 1910.134).
- Exposure Limits** : Not established for products as a whole. Refer to Section 2.

Section 9. Physical and Chemical Properties

- Physical Form** : Flexible solid.
- Odor** : No odor. Residual isobutane is colorless, with a gasoline-like or natural gas odor. Butane is reported to be detectable by odor at a range of 1262-5048 ppm (AIHA, 1989).
- Vapor Pressure** : Not applicable.
- Vapor Density** : Not applicable.
- Boiling Point** : Not applicable.
- Solubility in Water** : Insoluble.
- Density** : 0-35 lbs/ft³.

Section 10. Stability and Reactivity

Reactivity	: N/A
Stability	: This is a stable material.
Hazardous Polymerization	: Will not occur.
Incompatibilities	: Strong oxidizing agents.
Decomposition Products	: Carbon monoxide and other toxic gases are generated under combustion conditions.

Section 11. Toxicological Information

See Section 3 for potential health effects.

Section 12. Ecological Information

This product is inert to the environment and is not expected to exhibit any significant biodegradation.

Section 13. Disposal Considerations

Waste may be reused, recycled or buried in an approved landfill. Follow all regulatory requirements for disposal.

Section 14. Transport Information

DOT Shipping Requirements : Not regulated.

Section 15. Regulatory Information

OSHA Status	: This product is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.
CERCLA RQ	: None
SARA Title III: Section 302 Extremely Hazardous Substances	: None
Section 311/312 Hazard Categories	: Non-hazardous.
Sections 313 Hazard Categories	: None

Section 15. Regulatory Information *cont'd.*

- RCRA Status** : If discarded in its purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether the product should be classified as a hazardous waste (40 CFR 261.20-24).
- National Fire Protection Association (NFPA) Ratings** : Health 0
Flammability 1
Reactivity 0
- Canadian Regulations** : This product is not a "Controlled Product" under WHMIS.
- California Proposition 65** : This product may contain small percentages of chemical(s) known to the state of California to cause cancer and/or birth defects. All potential hazardous chemical with concentrations in the final product greater than 0.1% by weight are listed in Section 2.

Section 16. Other Information

- Date of Printing** : 05/05/2015
Date of Issue : 05/05/2015
Date of Previous Version : 06/06/2012
- Notice** : Each customer must determine whether the products discussed and the information contained in this document is appropriate for its use. NO WARRANTIES ARE GIVEN: ALL EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. It is the Customer's responsibility to ensure that workplace and disposal practices are compliant with any applicable laws. Information provided as a result of testing and analysis by D.S. Brown is accurate as of the date shown on this SDS sheet
- Conditions of use and applicable laws may change with time and differ from one location to another, therefore this information is subject to change without notice and D.S. Brown assumes no liability for use of or reliance upon this document. SDS sheets are intended for occupational use only. This information does not constitute a license under any patent or other proprietary right.

Distributed by: Bowman Construction Supply, 10801 E. 54th Avenue, Denver, CO 80239; Phone: (303) 696-8960



Bridge the World with Leading Infrastructure Solutions