



FLEXAMAT INFORMATION

Manufacturer: Motz Enterprises, Inc.
 Product Name: Flexamat®
 Address: 3153 Madison Road
 Cincinnati, Ohio 45209
 Telephone: 513-772-MOTZ (6689)
 Fax: 513-772-6690
 Contact: Matt Motz
 Email: Matt@Flexamat.com
 Website: www.Flexamat.com

CONSTRUCTION NOTES:

1. GRADE OUTFALL AREA SO THAT WATER WILL FLOW DOWN THE CENTER OF THE CHANNEL AND BE CONTAINED TO THE CHANNEL. ALL SUBGRADE SURFACES PREPARED FOR PLACEMENT OF MATS SHALL BE SMOOTH AND FREE OF ALL ROCKS, STICKS, ROOTS, OTHER PROTRUSIONS, OR DEBRIS OF ANY KIND. THE PREPARED SURFACE SHALL PROVIDE A FIRM UNYIELDING FOUNDATION FOR THE MATS WITH NO SHARP OR ABRUPT BREAKS IN THE GRADE .
2. APPLY SEED DIRECTLY TO THE PREPARED SOIL PRIOR TO FLEXAMAT INSTALLATION. USE SEED PER PROJECT SPECIFICATIONS.
3. PRIOR TO INSTALLING HEADWALL, ANCHOR TRENCH INITIAL LEADING EDGE OF MAT 18", FILL AND COMPACT ANCHOR TRENCH. INSTALL HEADWALL OVER MAT.
4. INSTALL FLEXAMAT ROLLS. AVAILABLE WIDTHS ARE 5.5', 8', 10', 12', & 16' AVAILABLE IN CUSTOM LENGTHS. A CONCRETE SAW SHALL BE USED TO CUT THE MAT TO EXACT SIZE AND SHAPE.
5. APPLICATIONS WHERE OUTFALLS FLOW INTO RETENTION PONDS, EXTEND FLEXAMAT A MINIMUM OF 3' BELOW LOW WATER ELEVATION.

DISTRIBUTOR
 Bowman Construction Supply
 10801 E. 54th Avenue
 Denver, CO 80239
 Phone: (303) 696-8960
www.bowmanconstructionsupply.com

FLEXAMAT®
 NEW OUTLET INSTALLATION
 DETAIL