



DeWitt Company Key Landscape Fabric & Groundcover Specifications

| DEWITT LANDSCAPE FABRIC & WOVEN GROUNDCOVER | ASTM | MECHANICAL PROPERTIES | | | | | ENDURANCE PROPERTIES | HYDRAULIC PROPERTIES | | | PHYSICAL PROPERTIES | | |
|--|------|------------------------------------|----------------------------------|----------------------------------|------------------|------------------|----------------------|----------------------------------|-------------------------------|--|--------------------------------------|----------------|----------------|
| | | Grab Tensile Strength (LBS) | Elongation % | Trapezoid Tear LBS | Puncture LBS | CBR Puncture LBS | Mullen Burst PSI | UV Stability % @ 500hrs | Permittivity sec-1 | Water Flow Rate gpm/sqft l/min/sqmt | Apparent Opening size US Sieve# (mm) | Weight oz/sqyd | thickness MILS |
| Pro5 Weed Barrier | ASTM | Warp - 100 Weft - 100 D-4632 | Warp - 15 Weft - 15 D-4632 | Warp - 40 Weft - 26 D-4533 | 65 D-4833 | D-3786 | 230 | >70% after 2500 Hrs D-4355 | 12 | D-4491 | | 5 | 32 |
| 20 YEAR WEED BARRIER | ASTM | Warp - 95 Weft - 50 D-4632 | Warp - 12 Weft - 12 D-4632 | Warp - 35 Weft - 20 D-4533 | 55 D-4833 | D-3786 | 240 | >70% after 2500 hrs D-4355 | 15 | D-4491 | | 4.1 | 24 |
| SUNBELT WOVEN GROUNDCOVER | ASTM | Warp - 175 Weft - 110 D-4632 | Warp - 25 Weft - 25 D-4632 | Warp - 80 Weft - 60 D-4533 | 50 D-4833 | D-3786 | 310 | >70% after 2500 hrs D-4355 | 12 (10'-15.5') 2.5 (3'-6') | D-4491 | | 3.2 | 21 |
| WEED BARRIER PRO BLACK | ASTM | MD - 55 CD - 50 D-5034 | MD - 40 CD - 80 D-5034 | MD - 25 D-4533 | | D-3786 | 75 | | 0.5 | 40 | | 3 | 24.4 |
| CONTRACTOR'S SELECT BLACK & GREY / TYPAR PREMIUM 3201 | ASTM | 73 D-4632 | >70 D-4632 | 25 D-4533 | 23 D-4833 | | | | 3 | 200 | 0.52 | 1.9 | 11.5 |
| CONTRACTOR'S SELECT PLUS BLACK / TYPAR PROFESSIONAL 3301 | ASTM | 120 D-4632 | >70 D-4632 | 46 D-4533 | 32 D-4833 | | | | 1.2 | 70 | 0.24 | 3 | 15 |
| CONTRACTOR'S SELECT PLUS GREY | ASTM | MD - 106 XD - 103 D-4632 | | MD - 53 XD - 47 D-4533 | | | | | | | | 2.5 | 13.4 |
| 12 YEAR WEED BARRIER | ASTM | MD - 55 CD - 50 D-5034 | MD - 40 CD - 80 D-5034 | MD - 25 D-4533 | | D-3786 | 75 | | 0.5 | 40 | | 3 | 24.4 |
| 6 YEAR WEED BARRIER | ASTM | MD - 18 CD - 15 D-5034 | MD - 100 CD - 200 D-5034 | | | | | | 1.5 | 110 | | 1.5 | 18 |
| 3 YEAR WEED BARRIER | ASTM | MD - 14 CD - 12 D-3776 | MD - 125 CD - 250 D-5034 | | | | | | 1.5 | 110 | | 1 | 16 |